






















# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Atlas Copco	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Atlas Copco BBC 43, BBC 44, BBC 45, BBC 100	R32	380	2.2	10	4BBC43-32R32-10380-23
	Atlas Copco BBC 51, BBC 52, BBC 54, BBC 120	R32 T38	380 390	2.9 3.4	10 10	4BBC51-38R32-10380-23 4BBC51-38T38-10390-23
	Atlas Copco BBE 57	T38	538	5.6	14	4BBE57-44T38-14538-23
	Atlas Copco COP 125, COP 130, COP 131	T38	380	3.3	14	4125-39T38-14380-23
	Atlas Copco COP 1032HD	R32	340	3.7	-	41032HD-45R32-0340-23
		R38	340	4.4	-	41032HD-55R32-0340-23
	Atlas Copco COP 1032	R32 R35 R38 T38	550 550 550 550	5.3 5.6 5.7 5.7	- - - -	41032-45R32-0550-23 41032-45R35-0550-23 41032-45R38-0550-23 41032-45T38-0550-23
	Atlas Copco COP 1036 COP 1038HB	R32 T38	500 500	4.3 4.7	- -	41036-38R32-0500-23 41036-38T38-0500-23
		T45	500	5.3	-	41036-45T45-0500-23
	Atlas Copco COP 1038HD COP 1238	R32 R38 T38	485 485 485	4.3 4.5 4.5	- - -	41238-38R32-0485-23 41238-38R38-0485-23 41238-38T38-0485-23











# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Atlas Copco	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Atlas Copco COP 1038HL	R32	575	4.9	-	41038HL-38R32-0575-23 41038HL-38T38-0575-23
		T38	575	5.2	-	
		T45	575	6.1	-	41038HL-45T45-0575-23
	Atlas Copco COP 1238	R32	500	4.0	-	41238-38R32-0500-23 41238-38T38-0500-23 41238-38R38-0485-23 41238-38T38-0485-23
		T38	500	4.4	-	
		R38	485	4.2	-	
		T38	485	4.2	-	
		T45	500	5.0	-	
		R32	575	4.9	-	41238-38R32-0575-23 41238-38R38-0575-23 41238-38T38-0575-23
		R38	575	5.0	-	
	T38	575	5.2	-		
		T38	575	5.7	-	41238-45T38-0575-23 41238-45T45-0575-23
	T45	575	6.1	-		
	Atlas Copco COP 1432, COP 1532, COP 1440, COP 1838 HD, COP 1838 ME	R32	435	3.9	-	41432-38R32-0435-23 41432-38R38-0435-23 41432-38T38-0435-23
		R38	435	4.2	-	
		T38	435	4.2	-	
	Atlas Copco COP 1432, COP 1532	R32	525	4.8	-	41432-38R32-0525-23 41432-38T38-0525-23
		T38	525	5.0	-	
		R32	341	4.7	-	41432-55R32-0341-23 41432-55R38-0341-23
	R38	341	5.2	-		
	Atlas Copco COP 1550, COP 1838ME/HE	T38	525	6.2	-	41550-52T38-0525-23 41550-52T45-0525-23 41550-52T51-0525-23
		T45	525	6.4	-	
		T51	525	6.8	-	

# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Atlas Copco, Boart and Furukawa	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Atlas Copco COP 1550 EX, COP 1838 EX	T38 T45 T51	730 730 730	10.1 10.5 10.7	- - -	41550EX-60T38-0730-23 41550EX-60T45-0730-23 41550EX-60T51-0730-23
	Atlas Copco COP 1840HE COP 1850	T45 T51	565 565	7.2 7.4	- -	41850-52T45-0565-23 41850-52T51-0565-23
	Atlas Copco COP 2150PG	T51	770	11.2	-	42150PG-52T51-0770-23
	Atlas Copco COP 2160EX	T45 T51	770 770	13.2 13.3	- -	42160EX-63T45-0770-23 42160EX-63T51-0770-23
	Atlas Copco COP 4050EX	ST68	805	69.6	-	44050EX-70ST68-0805-23
	Atlas Copco COP 4050MUX	ST68	835	69.9	-	44050MUX-90ST68-0835-23
	Boart HD 125, HD 150, HD 160	R38 T38	495 495	5.6 5.6	- -	4HD125-45R38-0495-23 4HD125-45T38-0495-23
	Furukawa M 120, PD 200	R32 R38 T38 T38	330 350 380 446	3.6 3.8 4.0 4.3	14.3 14.3 14.3 14.3	4M120-44R32-14330-23 4M120-44R38-14350-23 4M120-44T38-14380-23 4M120-44T38-14446-23
	Furukawa PD 200R	T38 T45	484 484	4.0 4.3	14.3 14.3	4PD200R-44T38-14484-23 4PD200R-44T45-14484-23
	Furukawa HD 260, HD 300	T38 T45	655 655	7.8 7.8	16 16	4HD260-45T38-16655-23 4HD260-45T45-16655-23










# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Furukawa, Gardner-Denver, Ingersoll-Rand and Montabert	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Furukawa HD 609	T38 T38 T45	620 690 620	6.2 6.5 6.9	- - -	4HD609-45T38-0620-23 4HD609-45T38-0690-23 4HD609-45T45-0620-23
	Furukawa HD 612	T45	710	9.2	-	4HD612-51T45-0710-23
	Furukawa HD 712	T45	788	11.2	-	4HD712-51T45-0788-23
	Gardner-Denver PR 123	R32 R38 T38 T45	380 380 380 380	3.6 3.9 3.9 4.2	14.3 14.3 14.3 14.3	4PR123-44R32-14380-23 4PR123-44R38-14380-23 4PR123-44T38-14380-23 4PR123-44T45-14380-23
	Ingersoll-Rand URD475, URD550, VL120, EVL130, VL140, F16	R32 R38 T38 T38	330 350 380 446	3.6 3.8 4.0 4.3	14 14 14 14	4VL120-44R32-14330-23 4VL120-44R38-14350-23 4VL120-44T38-14380-23 4VL120-44T38-14446-23
	Ingersoll-Rand YH 65, YH 80	T38 T45	500 500	5.8 6.1	19 19	4YH65-45T38-19500-23 4YH65-45T45-19500-23
	Ingersoll-Rand YH 65 RP, YH 70 RP, YH 75 RP, YH 80 RP	T45	700	8	19	4YH65RP-45T45-19700-23
	Montabert HC 40	R32 R38 T38	447 447 447	3.9 4.1 4.1	- - -	4HC40-38R32-0447-23 4HC40-38R38-0447-23 4HC40-38T38-0447-23
	Montabert HC 40	R32	270	4.1	-	4HC40-52R32-0270-23
	Montabert HC 40	R38	320	4.4	-	4HC40-55R38-0320-23










# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Montabert and SIG	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Montabert HC 80, HC 90, HC 105, HC 120	R32 R38 T38 T38	440 440 440 500	5.1 5.3 5.3 5.8	- - - -	4HC80-38R32-0440-23 4HC80-38R38-0440-23 4HC80-38T38-0440-23 4HC80-38T38-0500-23
	Montabert H 100	T38	540	5.6	14	4H100-45T38-14540-23
	Montabert HC 120, HC 150	T45	490	5.9	-	4HC120-45T45-0490-23
	Montabert HC 80R, HC 120R, HC 150R	T45 T51	670 670	8.3 8.3	- -	4HC80R-51T45-0670-23 4HC80R-51T51-0670-23
	Montabert HC 200	T51 T60	840 840	13.9 14.2	- -	4HC200-60T51-0840-23 4HC200-60T60-0840-23
	SIG HBM 50, HBM 100, HBM 120	R32	340	3.7	-	4HBM50-45R32-0340-23
	SIG HBM 100, HBM 120	R38	340	4.4	-	4HBM100-55R38-0340-23
	SIG HBM 50, HBM 100, HBM 120	R32	550	5.3	-	4HBM50-45R32-0550-23
	SIG HBM 101	R32	500	4.6	-	4HBM101-38R32-0500-23










# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Sandvik(Tamrock)	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Tamrock HL 300	R32	400	2.8	-	4HL300-32R32-0400-23
	Tamrock HL 300S	R32	245	2.8	-	4HL300S-45R32-0245-23
	Tamrock HLX 3	R32	324	3.8	-	4HLX3-45R32-0324-23
	Tamrock HLX 3F	R32	205	2.6	-	4HLX3F-45R32-0205-23
	Tamrock L400, L410, L500, L510, L550	R32	380	2.3	10	4L400-32R32-0380-23
	Tamrock HL 438, HL 538, HLR 438L, HLR 438T	R32 T38	380 400	3.2 3.6	12.7 12.7	4HL438-38R32-13380-23 4HL438-38T38-13400-23
	Tamrock HL 438LS, HL 438TS, HL 538, HL 538L, L 550S	R32 R38 T38 T38	450 450 455 545	4.1 4.3 4.3 4.8	- - - -	4HL538-38R32-0450-23 4HL538-38R38-0450-23 4HL538-38T38-0455-23 4HL538-38T38-0545-23
	Tamrock HL500-38, HL510-38	R32 T38	550 550	4.3 4.6	- -	4HL500-38R32-0550-23 4HL500-38T38-0550-23
	Tamrock HL 500-45, HL 510-45	R32 T38 T45	550 550 550	5.6 5.6 6.1	- - -	4HL500-45R32-0550-23 4HL500-45T38-0550-23 4HL500-45T45-0550-23

# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Sandvik(Tamrock)	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Tamrock HL 500S-38, HL 510S-38, HL 510B, HL 510HL	R32 R38 T38 R38 T38	460 460 460 500 500	3.9 4.1 4.1 4.3 4.3	- - - - -	4HL510B-38R32-0460-23 4HL510B-38R38-0460-23 4HL510B-38T38-0460-23 4HL510B-38R38-0500-23 4HL510B-38T38-0500-23
	Tamrock HL 500F, HL 510F	R32	350	3.6	-	4HL500F-45R32-0350-23
	Tamrock HL 550 SUPER, HL 560 SUPER, HL 510S-45	R38 T38 T45	500 500 500	5.5 5.5 5.6	- - -	4HL550-45R38-0500-23 4HL550-45T38-0500-23 4HL550-45T45-0500-23
	Tamrock HLX 5, HLX 5T	R32 R38 T38 R32 T38 T45	500 500 500 575 575 575	5.4 5.5 5.5 6.4 6.5 6.6	- - - - - -	4HLX5-45R32-0500-23 4HLX5-45R38-0500-23 4HLX5-45T38-0500-23 4HLX5-45R32-0575-23 4HLX5-45T38-0575-23 4HLX5-45T45-0575-23
	Tamrock HLX5 PE-45	R32 T38	575 575	6.3 6.4	- -	4HLX5PE-45R32-0575-23 4HLX5PE-45T38-0575-23
	Tamrock HL 600-45, HL 600S-45	T38 T45 R32 T38 T45	600 600 525 525 525	6.7 6.7 5.9 6.0 6.1	- - - - -	4HL600-45T38-0600-23 4HL600-45T45-0600-23 4HL600-45R32-0525-23 4HL600-45T38-0525-23 4HL600-45T45-0525-23
	Tamrock HL 600-52, HL 600S-52	T45 T51	650 650	8.0 8.0	- -	4HL600-52T45-0650-23 4HL600-52T51-0650-23
	Tamrock HL 645, HL 645S	T38 T45	600 600	6.6 6.8	- -	4HL645-45T38-0600-23 4HL645-45T45-0600-23
	Tamrock HL 650-45, HL 700-45, HL 700T-45, HL 710-45, HL 800T-45	T38 T45	600 600	7.3 7.8	- -	4HL650-45T38-0600-23 4HL650-45T45-0600-23

# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Sandvik(Tamrock)	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Tamrock HL 650-52, HL 700-52, HL 710-52, HL 800T-52	T38 T45 T51	600 600 600	8.3 8.8 8.8	- - -	4HL650-52T38-0600-23 4HL650-52T45-0600-23 4HL650-52T51-0600-23
	Tamrock HL 850 HL 850S	T45 T51	670 670	9.8 10.1	- -	4HL850-52T45-0670-23 4HL850-52T51-0670-23
	Tamrock HL 1000-52, HL 1000S-52	T45 T51 T45 T51	670 670 590 590	10.3 11.0 8.7 8.7	- - - -	4HL1000-52T45-0670-23 4HL1000-52T51-0670-23 4HL1000-52T45-0590-23 4HL1000-52T51-0590-23
	Tamrock HL 1000-60	T51 T60	670 670	13.3 13.4	- -	4HL1000-60T51-0670-23 4HL1000-60T60-0670-23
	Tamrock HL 1000-80	T60	670	20.9	-	4HL1000-80T60-0670-23
	Tamrock HL 1000S-80	ST58 ST68	635 640	18.2 19.1	- -	4HL1000S-80ST58-0635-23 4HL1000S-80ST68-0640-23
	Tamrock HL 1000 PE-52	T51	840	14.2	-	4HL1000PE-52T51-0840-23
	Tamrock HL 1000 PE-65, HL 1500 PE-65, HL 1560 T-65	T51 T60	760 760	16.8 16.9	- -	4HL1000PE-65T51-0760-23 4HL1000PE-65T60-0760-23
	Tamrock HL 1500-52, HL 1500T-52	T51	710	11.9	-	4HL1500-52T51-0710-23

# Shank Adapter

İKSİS MAKİNA SAN. VE TİC. LTD. ŞTİ.

Sandvik(Tamrock), Others	Rock drill	Thread	Length (mm)	Weight (Kg)	Flushing (mm)	RC-Tech (P/N)
	Tamrock HL 1500-60, HL 1500T-60	T51 T60	760 760	16.1 16.1	- -	4HL1500-60T51-0760-23 4HL1500-60T60-0760-23
	Tamrock HL 1500-T80	T60	760	22.9	-	4HL1500-80T60-0760-23
	Tamrock HL 1500-S80	ST58 ST68	635 635	18.8 18.9	- -	4HL1500-80ST58-0635-23 4HL1500-80ST68-0635-23
	Tamrock HL 1500-SPE90	ST58 ST68	635 635	21.8 21.9	- -	4HL1500-90ST58-0635-23 4HL1500-90ST68-0635-23
		HL64	1180	35.6	-	40THER-70HL64-1180-23
		R32	410	3.1	-	40THER-35R32-410-23